

LevelOne 6-Port Gigabit Industrial Switch, 1 x SFP, 1 x SFP/RJ45 Combo, -40°C to 75°C, DIN-Rail

Brand: LevelOne Product code: IES-0600


Product name: 6-Port Gigabit Industrial Switch, 1 x SFP, 1

x SFP/RJ45 Combo, -40°C to 75°C, DIN-Rail

4x 10/100/1000Base-T, 1x SFP/RJ45 Combo, 1x Gigabit SFP, 1024 MAC, 12 Gbps, 10K Jumbo Frame

LevelOne 6-Port Gigabit Industrial Switch, 1 x SFP, 1 x SFP/RJ45 Combo, -40°C to 75°C, DIN-Rail:

LevelOne IES-0600 Industry Ethernet Switch provides 4 ports 10/100/1000Base plus 2 port Gigabit SFP to enable high speed network at mission-critical environment. With the industrial standard DIN-rain mount; this switch can be easily installed in the cabinet, plus the clearly visible status LEDs provide simple monitoring of port link activity. Moreover, the SFP slots support pluggable modules that enabling you to choose from a variety of transceivers.



- 4 10/100/1000Base-T ports
- 1 Gigabit Combo + 1 Gigabit SFP(100/1G) slot
- 1000 Mbps-Full-duplex, 10/100Mbps-Full/Half-duplex,
- Auto-Negotiation, Auto-MDI/MDIX
- 40°C to 75°C (- 40°F to 167°F) operating temperature range
- DIN-Rail mount installation
- Metal case design and compliant with IP30 standard

Ports & interfaces		Power	
Basic switching RJ-45 Ethernet ports	5 ₄	Power protection features	Overload, Reverse polarity
quantity * Basic switching RJ-45 Ethernet ports Gigabit Ethernet (10/100/1000)		Power over Ethernet (PoE)	
type *	' Gigabit Ethernet (10/100/1000)	Power over Ethernet (PoE) *	x
SFP module slots quantity	1	Other features	
Network		Terminal block port	✓
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Operational conditions	
10G support *	×	Operating temperature (T-T)	-40 - 75 °C
Full duplex	✓	Storage temperature (T-T)	-40 - 85 °C
Flow control support	✓	Operating relative humidity (H-H)	5 - 95%
Auto MDI/MDI-X	✓	Storage relative humidity (H-H)	5 - 95%
Auto-negotiation	✓	Weight & dimensions	
Data transmission		Width	40 mm
Switching capacity *	12 Gbit/s	Depth	105 mm
MAC address table *	1024 entries	Height Weight	38 mm 720 g
Store-and-forward	✓		720 g
Jumbo frames	10000	Packaging content	
Packet forwarding rate (1 Gbps)	1488000 pps	Quick start guide	✓
Packet forwarding rate (100 Mbps)	148000 pps	Packaging data	
Packet forwarding rate (10 Mbps)	14880 pps	Package type	Box
Packet buffer memory	1 MB	Package width	215 mm
Design		Package depth	165 mm
Product colour	Black	Package height	65 mm
Housing material	Metal	Package weight	120 g
LED indicators	Activity, Link, Power		
International Protection (IP) code	IP30		
Wall mountable	/		
DIN rail mounting	✓		
Power			
Input voltage	5 - 56 V		

Certificates		
Certification	FCC Part 15 Subpart B Class A CE EN 55022 Class A EN61000-4-2 (ESD) Level 3 EN61000-4-3 (RS) Level 3 EN61000-4-4 (EFT) Level 3 EN61000-4-5 (Surge) Level 3 EN61000-4-6 (CS) Level 3 EN61000-4-8 (Magnetic Field) Level 3 UL508 (Pending) EN 50121-4 (Pending) IEC 60068-2-27 IEC 60068-2-32 IEC 60068-2-6 UL 508	
Logistics data		
Country of origin Harmonized System (HS) code	Taiwan 85176990	





4015867188491

4015867224250

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.