

## CyberPower PR3000ELCDSL uninterruptible power supply (UPS) Line-Interactive 3 kVA 2700 W 9 AC outlet(s)

**Brand :** CyberPower

**Product code:** PR3000ELCDSL

**Product name :** PR3000ELCDSL

3000VA, 2700W, 8 x IEC 320 C13 & 1 x IEC 320 C19 Out

CyberPower PR3000ELCDSL. UPS topology: Line-Interactive, Output power capacity: 3 kVA, Output power: 2700 W. AC outlet types: C13 coupler, C19 coupler, Power plug: C20 coupler, AC outlets quantity: 9 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 9 Ah, Battery voltage: 12 V. Form factor: Tower, Product colour: Black, Display type: LCD. Width: 170 mm, Depth: 432 mm, Height: 221 mm



| Features                           |                          | Ports & interfaces                  |                             |
|------------------------------------|--------------------------|-------------------------------------|-----------------------------|
| UPS topology *                     | Line-Interactive         | Emergency Power Off (EPO) connector | ✓                           |
| Output power capacity *            | 3 kVA                    | <b>Battery</b>                      |                             |
| Output power *                     | 2700 W                   | Battery technology                  | Sealed Lead Acid (VRLA)     |
| Waveform *                         | Sine                     | Battery capacity                    | 9 Ah                        |
| Input operation voltage (min) *    | 160 V                    | Battery voltage                     | 12 V                        |
| Input operation voltage (max) *    | 283 V                    | Number of batteries supported       | 4                           |
| Input frequency *                  | 50/60 Hz                 | Typical backup time at full load    | 3 min                       |
| Output frequency                   | 50/60 Hz                 | Typical backup time at half load    | 12 min                      |
| Automatic Voltage Regulation (AVR) | ✓                        | Battery recharge time               | 8 h                         |
| Surge energy rating                | 405 J                    | Automatic battery test              | ✓                           |
| Emergency Power Off (EPO)          | ✓                        | <b>Design</b>                       |                             |
| EMI/RFI noise filtering            | ✓                        | Form factor *                       | Tower                       |
| Surge protection                   | ✓                        | Product colour *                    | Black                       |
| Power protection features          | Overload                 | Display type                        | LCD                         |
| Audible alarm(s)                   | ✓                        | LED indicators                      | ✓                           |
| Auto-restart                       | ✓                        | <b>Weight &amp; dimensions</b>      |                             |
| Ports & interfaces                 |                          | Width                               | 170 mm                      |
| AC outlet types                    | C13 coupler, C19 coupler | Depth                               | 432 mm                      |
| Power plug                         | C20 coupler              | Height                              | 221 mm                      |
| AC outlets quantity                | 9 AC outlet(s)           | Weight                              | 24.5 kg                     |
| USB 2.0 ports quantity             | 1                        | <b>Packaging data</b>               |                             |
| Serial ports quantity              | 1                        | Bundled software                    | PowerPanel Business Edition |
|                                    |                          | <b>Other features</b>               |                             |
|                                    |                          | Output voltage                      | 230 V                       |



4712364146367

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.