

CyberPower CP1200EIPFCRM2U uninterruptible power supply (UPS) Line-Interactive 12 kVA 720 W 8 AC outlet(s)

Brand : CyberPower

Product code: CP1200EIPFCRM2U

Product name : CP1200EIPFCRM2U



CyberPower CP1200EIPFCRM2U. UPS topology: Line-Interactive, Output power capacity: 12 kVA, Output power: 720 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 3.4 min, Typical backup time at half load: 11.6 min. Form factor: Rackmount, Product colour: Black, Housing material: Metal. Compliance certificates: CE, RoHS



Features		Ports & interfaces	
UPS topology *	Line-Interactive	RS-232 ports	1
Output power capacity *	12 kVA	Ethernet LAN (RJ-45) ports	2
Output power *	720 W	Battery	
Waveform *	Pure sine	Battery technology	Sealed Lead Acid (VRLA)
Input operation voltage (min) *	169 V	Number of batteries supported	1
Input operation voltage (max) *	271 V	Typical backup time at full load	3.4 min
Input frequency *	50/60 Hz	Typical backup time at half load	11.6 min
Output frequency	50/60 Hz	Hot-swap battery	✓
Output frequency regulation	1 Hz	Design	
Automatic Voltage Regulation (AVR)	✓	Form factor *	Rackmount
Heat dissipation	17.1 BTU/h	Housing material	Metal
Power factor	0.6	Rack capacity	2U
Power Factor Correction (PFC) type	Active	Cooling type	Active
ECO mode	✓	Built-in fan	✓
EMI/RFI noise filtering	✓	Product colour *	Black
Surge protection	✓	Control type	Buttons
Power protection features	Over voltage, Overload	Display type	LCD
Power source type	AC	LED indicators	✓
Detachable power cord	✓	Operational conditions	
Ports & interfaces		Operating temperature (T-T)	0 - 40 °C
AC outlet types	C13 coupler	Operating relative humidity (H-H)	0 - 95%
Power plug	C14 coupler	Certificates	
AC outlets quantity	8 AC outlet(s)	Compliance certificates	CE, RoHS
USB port	✓	Weight & dimensions	
USB 2.0 ports quantity	1	Width	433 mm
USB port type	USB Type-B	Depth	274 mm
Serial interface	✓		
Serial interface type	RS-232		

Ports & interfaces		Weight & dimensions	
Serial ports quantity	1	Height	86 mm
		Weight	11.6 kg
		Other features	
		Battery type	RBP0181



4711027798233

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-MAY-2025. Prints or copies of Information are only valid on the printed Publication date