QNAP

QNAP TS-932PX-4G NAS Tower Annapurna Labs Alpine AL-324 4 GB DDR4 80 TB HDD QNAP Turbo System Black

Brand: QNAP Product code: TS-932PX-4G/80TB-IWP

Product name: TS-932PX-4G

- Two 10GbE SFP+ and two 2.5GbE RJ45 network ports empower bandwidth-demanding tasks and accelerate file sharing
- HBS provides comprehensive backup and data recovery; QuDedup deduplicates the data at the source to optimize storage and bandwidth usage, while reducing backup times
- Snapshots record your system status, allowing you to protect files and data from accidental deletion and malware attacks
- Cloud storage gateways realize hybrid cloud applications by working with the cache space reserved on NAS to ensure low-latency data access to the cloud
- Qtier auto-tiering technology and SSD caching enable constant storage optimization
- Increase the storage capacity of the TS-932PX with QNAP TR RAID expansion enclosures or TL JBOD Alpine AL-324 1.7GHz, 4 GB DDR4, 512 MB, 5x 3.5, 4x 2.5", 2x 2.5G LAN, 2x 10G SFP+, 3x USB 3.2, 182.7x224.6x224.1 mm





Storage		Design	
Supported storage drive interfaces	Serial ATA III	Chassis type *	Tower
Storage drive sizes supported	2.5,3.5"	Cooling type *	Active
RAID support *	✓	Product colour	Black
RAID levels	0, 1, 5, 6, 10, 50, 60, JBOD	Number of fans	1 fan(s)
Online RAID migration	✓	Fan diameter	14 cm
Online RAID expansion	✓	LED indicators	HDD, LAN, SSD, Status, USB
RAID rebuild	✓	Cable lock slot	•
Hot-swap drive bays	✓	Cable lock slot type	Kensington
Supported file systems	FAT32, HFS+, NTFS, ext3, ext4	Performance	
Storage drives installed *	✓	Type *	NAS
Total installed storage capacity *	80 TB	Device class *	Small & Medium Business
Number of storage drives supported	١٩	Backup function *	✓
*	, and the second	Backup features	Cloud, iSCSI LUN
Installed storage drive type *	HDD	Buzzer	✓
Supported storage drive types *	HDD & SSD	Multilingual support	✓
Bad block scan	✓	Snapshot	✓
Disk roaming	✓	Web-based management	✓
Processor Processor manufacturer *	Annapurna Labs	Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SNMPv2, SNMPv3, SSH, SSL/TLS
Processor family *	Annapurna Labs	Access Control List (ACL)	✓
Processor model *	Alpine AL-324	Reset button	✓
Processor frequency *	1.7 GHz	On/off switch	✓
Processor architecture	ARM Cortex-A57	Built-in FTP server	✓
Memory Internal memory *	4 GB	Browser supported	Apple Safari 7+, Google Chrome, Microsoft Internet Explorer 10+, Mozilla Firefox
Internal memory type	DDR4	System log	✓
Maximum RAM supported	16 GB	Hot spare	✓
Memory slots Memory form factor	1 SO-DIMM	S.M.A.R.T. support	/
Memory form factor Flash memory	50-DIMM 512 MB	Share folder	CIFS/SMB
	סוגן זינט	USB copy function	✓
Network		Software	
Ethernet LAN *	100 1000 2500 10000 MICH	Operating system installed *	QNAP Turbo System
Ethernet LAN data rates	100,1000,2500,10000 Mbit/s	Operating system version	4.4.2

Network		Software	
Ethernet LAN data rate supported (max)	10000 Mbit/s	Windows operating systems supported	Windows 10, Windows 7, Windows 8
DHCP client	✓	Linux operating systems supported	✓
DHCP server	✓	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.14 Mojave, Mac OS X
Jumbo frames support	✓		
iSCSI support	✓		
Wake-on-LAN ready	✓	Server operating systems supported	10.15 Catalina Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Supported network protocols	FTP, SFTP, TFTP, ec, OpenVPN, QBelt		
Link aggregation	✓		
Load balancing system	✓	Power	
Dynamic DNS (DDNS)	✓	Power supply location	External
WLAN adapter supported	✓	Power supply unit (PSU) capacity	120 W
Ports & interfaces		Number of power supply units	1
USB port *	,	AC input voltage	100 - 240 V
USB 3.2 Gen 1 (3.1 Gen 1) Type-A	-	Fan voltage	12 V
ports quantity	3	Weight & dimensions	
Fiber ports quantity	2	Width *	224.6 mm
Fiber optic connector	SFP+	Depth *	224.1 mm
Ethernet LAN (RJ-45) ports *	2	Height *	182.7 mm
		Packaging content	
		External power adapter	✓
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 5 - 95%

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.