



## QNAP TS-932PX-4G NAS Tower Annapurna Labs Alpine AL-324 4 GB DDR4 30 TB HDD QNAP Turbo System Black

**Brand :** QNAP

**Product code:** TS-932PX-4G/30TB-IW

**Product name :** TS-932PX-4G

- Two 10GbE SFP+ and two 2.5GbE RJ45 network ports empower bandwidth-demanding tasks and accelerate file sharing
  - HBS provides comprehensive backup and data recovery; QuDedup deduplicates the data at the source to optimize storage and bandwidth usage, while reducing backup times
  - Snapshots record your system status, allowing you to protect files and data from accidental deletion and malware attacks
  - Cloud storage gateways realize hybrid cloud applications by working with the cache space reserved on NAS to ensure low-latency data access to the cloud
  - Qtier auto-tiering technology and SSD caching enable constant storage optimization
  - Increase the storage capacity of the TS-932PX with QNAP TR RAID expansion enclosures or TL JBOD
- Alpine AL-324 1.7GHz, 4 GB DDR4, 512 MB, 5x 3.5", 4x 2.5", 2x 2.5G LAN, 2x 10G SFP+, 3x USB 3.2, 182.7x224.6x224.1 mm



| Storage                              |                               | Design                       |                                                                                  |
|--------------------------------------|-------------------------------|------------------------------|----------------------------------------------------------------------------------|
| Supported storage drive interfaces   | Serial ATA III                | Chassis type *               | Tower                                                                            |
| Storage drive sizes supported        | 2.5,3.5"                      | Cooling type *               | Active                                                                           |
| RAID support *                       | ✓                             | Product colour               | Black                                                                            |
| RAID levels                          | 0, 1, 5, 6, 10, 50, 60, JBOD  | Number of fans               | 1 fan(s)                                                                         |
| Online RAID migration                | ✓                             | Fan diameter                 | 14 cm                                                                            |
| Online RAID expansion                | ✓                             | LED indicators               | HDD, LAN, SSD, Status, USB                                                       |
| RAID rebuild                         | ✓                             | Cable lock slot              | ✓                                                                                |
| Hot-swap drive bays                  | ✓                             | Cable lock slot type         | Kensington                                                                       |
| Supported file systems               | FAT32, HFS+, NTFS, ext3, ext4 | Performance                  |                                                                                  |
| Storage drives installed *           | ✓                             | Type *                       | NAS                                                                              |
| Total installed storage capacity *   | 30 TB                         | Device class *               | Small & Medium Business                                                          |
| Number of storage drives supported * | 9                             | Backup function *            | ✓                                                                                |
| Installed storage drive type *       | HDD                           | Backup features              | Cloud, iSCSI LUN                                                                 |
| Supported storage drive types *      | HDD & SSD                     | Buzzer                       | ✓                                                                                |
| Bad block scan                       | ✓                             | Multilingual support         | ✓                                                                                |
| Disk roaming                         | ✓                             | Snapshot                     | ✓                                                                                |
| Processor                            |                               | Web-based management         | ✓                                                                                |
| Processor manufacturer *             | Annapurna Labs                | Security algorithms          | 256-bit AES, FIPS 140-2, HTTPS, SNMPv2, SNMPv3, SSH, SSL/TLS                     |
| Processor family *                   | Annapurna Labs                | Access Control List (ACL)    | ✓                                                                                |
| Processor model *                    | Alpine AL-324                 | Reset button                 | ✓                                                                                |
| Processor frequency *                | 1.7 GHz                       | On/off switch                | ✓                                                                                |
| Processor architecture               | ARM Cortex-A57                | Built-in FTP server          | ✓                                                                                |
| Memory                               |                               | Browser supported            | Apple Safari 7+, Google Chrome, Microsoft Internet Explorer 10+, Mozilla Firefox |
| Internal memory *                    | 4 GB                          | System log                   | ✓                                                                                |
| Internal memory type                 | DDR4                          | Hot spare                    | ✓                                                                                |
| Maximum RAM supported                | 16 GB                         | S.M.A.R.T. support           | ✓                                                                                |
| Memory slots                         | 1                             | Share folder                 | CIFS/SMB                                                                         |
| Memory form factor                   | SO-DIMM                       | USB copy function            | ✓                                                                                |
| Flash memory                         | 512 MB                        | Software                     |                                                                                  |
| Network                              |                               | Operating system installed * | QNAP Turbo System                                                                |
| Ethernet LAN *                       | ✓                             | Operating system version     | 4.4.2                                                                            |
| Ethernet LAN data rates              | 100,1000,2500,10000 Mbit/s    |                              |                                                                                  |

| Network                                         |                                     | Software                            |                                                                                                                                                       |
|-------------------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ethernet LAN data rate supported (max)          | 10000 Mbit/s                        | Windows operating systems supported | Windows 10, Windows 7, Windows 8                                                                                                                      |
| DHCP client                                     | ✓                                   | Linux operating systems supported   | ✓                                                                                                                                                     |
| DHCP server                                     | ✓                                   | Mac operating systems supported     | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina |
| Jumbo frames support                            | ✓                                   |                                     |                                                                                                                                                       |
| iSCSI support                                   | ✓                                   |                                     |                                                                                                                                                       |
| Wake-on-LAN ready                               | ✓                                   | Server operating systems supported  | Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019                                         |
| Supported network protocols                     | FTP, SFTP, TFTP, ec, OpenVPN, QBelt |                                     |                                                                                                                                                       |
| Link aggregation                                | ✓                                   |                                     |                                                                                                                                                       |
| Load balancing system                           | ✓                                   | Power                               |                                                                                                                                                       |
| Dynamic DNS (DDNS)                              | ✓                                   | Power supply location               | External                                                                                                                                              |
| WLAN adapter supported                          | ✓                                   | Power supply unit (PSU) capacity    | 120 W                                                                                                                                                 |
| Ports & interfaces                              |                                     | Number of power supply units        | 1                                                                                                                                                     |
| USB port *                                      | ✓                                   | AC input voltage                    | 100 - 240 V                                                                                                                                           |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 3                                   | Fan voltage                         | 12 V                                                                                                                                                  |
| Fiber ports quantity                            | 2                                   | Weight & dimensions                 |                                                                                                                                                       |
| Fiber optic connector                           | SFP+                                | Width *                             | 224.6 mm                                                                                                                                              |
| Ethernet LAN (RJ-45) ports *                    | 2                                   | Depth *                             | 224.1 mm                                                                                                                                              |
|                                                 |                                     | Height *                            | 182.7 mm                                                                                                                                              |
|                                                 |                                     | Packaging content                   |                                                                                                                                                       |
|                                                 |                                     | External power adapter              | ✓                                                                                                                                                     |
|                                                 |                                     | Operational conditions              |                                                                                                                                                       |
|                                                 |                                     | Operating temperature (T-T)         | 0 - 40 °C                                                                                                                                             |
|                                                 |                                     | Operating relative humidity (H-H)   | 5 - 95%                                                                                                                                               |

## Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.