

CyberPower OLS6000ERTXL3U uninterruptible power supply (UPS) Double-conversion (Online) 6 kVA 5400 W 1 AC outlet(s)

Brand : CyberPower

Product code: OLS6000ERTXL3U

Product name : OLS6000ERTXL3U



Single Phase, Online Double Conversion, Online ECO Mode Efficiency > 96%, 110 ~ 276V

CyberPower OLS6000ERTXL3U uninterruptible power supply (UPS) Double-conversion (Online) 6 kVA 5400 W 1 AC outlet(s):

CyberPower OLS6000ERTXL3U is a high-performance UPS featuring online double-conversion topology, which provides seamless Pure Sine Wave power for mission-critical devices such as NAS and servers, DVRs/surveillance systems, transportation and infrastructure, and emergency systems. It's typically integrated in the back office, server room, and data center environment.

Selected product is equipped with a Maintenance Bypass Switch. By flipping the switch, the power supply is safely transferred to utility. This allows service personnel to carry out fast on-site maintenance without having to shut down any connected equipment.



Features		Ports & interfaces	
UPS topology *	Double-conversion (Online)	Serial interface	✓
Output power capacity *	6 kVA	Serial interface type	RS-232
Output power *	5400 W	RS-232 ports	1
Waveform *	Pure sine	Design	
Input operation voltage (min) *	110 V	Form factor *	Rackmount/Tower
Input operation voltage (max) *	276 V	Housing material	Metal
Input frequency *	50/60 Hz	Product colour *	Black
Output operation voltage (min)	208 V	Display type	LCD
Output operation voltage (max)	240 V	LED indicators	✓
Output frequency	50/60 Hz	Operational conditions	
Output voltage regulation	0.1%	Operating temperature (T-T)	0 - 40 °C
Surge energy rating	445 J	Storage temperature (T-T)	-15 - 45 °C
Number of output phases	1	Operating relative humidity (H-H)	0 - 90%
Efficiency (ECO mode)	96%	Storage relative humidity (H-H)	0 - 95%
Power factor	0.9	Operating altitude	0 - 2000 m
Input power factor	0.99	Non-operating altitude	0 - 15000 m
Crest factor	3:1	Certificates	
ECO mode	✓	Compliance certificates	RoHS
Ports & interfaces		Certification	CE
AC outlets quantity	1 AC outlet(s)	Weight & dimensions	
USB port	✓	Width	438 mm
		Depth	680 mm
		Height	130.5 mm
		Weight	17.5 kg



4712856270914

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.