

EQUIP SAFE OUTDOOR 19' CABINET, 20U, 600X600MM, RAL7035 GREY

Product Images





Short Description

- 20U cabinet, designed for optimal performance in every space
- 600X600MM Outdoor Cabinet
- Ships preassembled for easy setup at your location
- The cabinet comes with a robust steel frontdoor to prioritize security and long-lasting durability

Description

The "Safe Outdoor" Cabinet Line presents the 483 mm (19") IP55 Outdoor Wall Mount Cabinets, tailored for industrial use. Adhering to the IP55 safety standard as per EN 60529, they offer resistance against both water and dirt infiltration. Enhanced security is ensured with a 3-point-locking system complemented by a lockable swing handle and insulated cable entry points. The cabinets also feature integrated air ventilation slots for fresh air circulation, maintaining protection against water and dust as per IP54 standards. These cabinets are ideal for locations exposed to environmental elements like rain, dust, sleet, snow, and splashing water. For more flexibility, these cabinets can be paired with a plinth for standalone setups. When using the plinth, rear mounting holes can be sealed using plugs sourced from the cabinet's base.

Additional Information

Number of cartons per pallet	8 piece
Pallet net weight	18000 gram
Pallet gross volume	3937700 cubic_centimeter
Package volume	23691150 cubic_centimeter
Maximum number of stacking cartons	8 piece
Pallet net length	1300 millimeter
Pallet net width	1300 millimeter
Pallet net height	2330 millimeter
Manual	No
Mounting kit	No
Size (imperial)	19.5 inch
Height	1068 millimeter
Width	600 millimeter
Depth	600 millimeter
Material thickness	3.5 millimeter
Inner height	889 millimeter
Inner width	595 millimeter
Minimum rack depth supported	260 millimeter
Maximum rack depth supported	535 millimeter
Inner depth	595 millimeter
Weight	58000 gram
Wall mountable	Yes
Key lock	Yes
Housing material	Steel
Built-in UPS	No
Rack rails	No

Frame type	Closed
Assembly required	No
Preassembled	Yes
Soundproof	No
Castor wheels	No
Type	Wall mounted rack
Rack capacity	20U
Removable back door	No
Removable front door	Yes
Back door construction	Steel
Front door construction	Steel
Side panel construction	Steel
Side panel key lock	No
Back door key lock	No
Front door key lock	Yes
Side panels included	No
Rack rail thickness	1.5 millimeter
Stabilizing foot screw	No
Adjustable stand	Yes
Monitoring	No
Main PDU	No
Product design	2-Post
Cooling type	Passive
Door opening angle	140 degree
Mounting hole shape	Square
Removable side panels	No
Number of layers per pallet	2 piece

Pallet gross weight	506200 gram
Harmonized System (HS) code	853710980019
Carbon footprint	9.918 kilogram
Quantity per pallet	8 piece
Sustainability compliance	Yes
Screws included	No
Wall mounting kit	Yes
Temperature sensor	No
Quantity per pack	8 piece
Plinth panel	No
Nuts included	Yes
Number of nuts	1
Package depth	630 millimeter
Package height	1090 millimeter
Package width	690 millimeter
Grounding kit	Yes
Quick installation guide	No
Package weight	3025 gram
Adjustable feet	No
Adjustable depth	No
Cable management	No
Color	Light Grey
EAN	4015867232453
Model Number	ESO-20-6060-G

