

HDMI® Cables Selection Guide









Untangle Cable Confusion

With An Organized
Buying Experience from
C2G HDMI Cables.

Streamline your connectivity solutions with our highquality line of HDMI® cables meticulously organized for you. Our thoughtfully curated product offering ensures quick and hassle-free selection, saving you valuable time. Experience superior convenience and efficiency in your buying process, as we prioritize ease of access and top-notch performance in every cable we deliver.







New Series Easy as 1-2-3

We've reorganized our HDMI cable lines into three series (Performance, Plus and Core) to make it easier for you to find the cable you need. Visit our website at www.legrandav.com/c2g to explore the full range of C2G HDMI cables and find the perfect solution for your needs.



Premium Reliability.



active copper cables, and active optical cables. When failure is not an option, count on C2G Performance Series HDMI Cables for total reliability.

Your go-to for certified cables,



Your go-to for basic in-wall cables, plenum cables, and slim cables. A broad selection of cables for a variety of applications - at the right price.





This is your go-to for basic 4K HDMI cable - offering reliable connectivity at the most affordable price. C2G's Core Series provides you with reliable cables for office or commercial use.





Premium Reliability.

Your go-to for cables, active copper cables, and active optical cables. When failure is not an option, count on C2G Performance Series for total reliability.

C2G Performance Series HDMI® cables are designed to meet the needs of commercial AV applications, from computers to projectors and monitors, AV presentation furniture, or in-wall applications. C2G'S Performance Series includes HDMI-certified cables, flexible cables for tight spaces, Ultra High Speed Cables for 8K resolutions, and active optical HDMI cables for extended lengths needs.

- 100% Tested All Performance Series HDMI passive cables are tested at the production line to ensure they meet our standards—providing the peace of mind they will perform as expected.
- Commercial Grade Connectors Overmolding with integrated finger
 grips on all sides makes these cables easy to insert and remove in limited
 access spaces and high-density environments. Additionally, the gripping
 connector shell provides two times the port retention of a standard
 connector, reducing the chances of an accidental disconnect.

- TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 ALTITIDE: 4.00 m.

 STACE: 5-01

 TIME: 0.000.22 SPACED. 25790 Lmh.

 TIME: 0.000.22 SPACED. 2
- In-wall Rated Jacket Ensures safe and compliant cable installation within walls.
- Lifetime Warranty C2G Performance Series Cables are backed by a lifetime warranty* for extra peace of mind.

PERFORMANCE SERIES Premium High Speed HDMI® Cable with Ethernet. For applications requiring HDMI certification.

• Tested to comply with HDMI Certification, this premium line provides the highest level of guarantee, making it the preferred choice for mission-critical applications



Item #	Length	Certification	Connector	Active/Passive	Maximum Bandwidth	Maximum Resolution	Maximum Refresh Rate	Cable Diameter	Minimum Bend Radius	Jacket Rating
50181 or CG50181†	3ft (0.9m)	Premium	Gripping	Passive	18 Gbps	4K	60Hz	6mm	70mm	CMG, FT4
50182 or CG50182†	6ft (1.8m)	Premium	Gripping	Passive	18 Gbps	4K	60Hz	6mm	70mm	CMG, FT4
50184 or CG50184†	10ft (3m)	Premium	Gripping	Passive	18 Gbps	4K	60Hz	6mm	70mm	CMG, FT4
50185 or CG50185†	12ft (3.7m)	Premium	Gripping	Passive	18 Gbps	4K	60Hz	6mm	70mm	CMG, FT4
50186 or CG50186†	15ft (4.6m)	Premium	Gripping	Passive	18 Gbps	4K	60Hz	6.5mm	75mm	CMG, FT4
50188 or CG50188†	20ft (6.1m)	Premium	Gripping	Passive	18 Gbps	4K	60Hz	9.5mm	90mm	CMG, FT4
C2G50196	25ft (7.6m)	Premium	Gripping	Passive	18 Gbps	4K	60Hz	9.0mm	90mm	CMG, FT4



^{*} Performance Series Active Optical HDMI Cables and Performance Series Ultra Flexible Active Cables offer a 5-Year Warranty.





PERFORMANCE SERIES Ultra Flexible High Speed HDMI® Cable with Ethernet. Your go-to 4K cable for tight spaces.







Item #	Length	Certification	Connector	Active/Passive	Maximum Bandwidth	Maximum Resolution	Maximum Refresh Rate	Cable Diameter	Minimum Bend Radius	Jacket Rating
C2G10373	1ft (0.3m)	No	Gripping	Passive	18 Gbps	4K	60Hz	6mm	48mm	CMG, FT4
C2G10374	1.5ft (0.5m)	No	Gripping	Passive	18 Gbps	4K	60Hz	6mm	48mm	CMG, FT4
C2G10375	2ft (0.6m)	No	Gripping	Passive	18 Gbps	4K	60Hz	6mm	48mm	CMG, FT4
C2G10376	3ft (0.9m)	No	Gripping	Passive	18 Gbps	4K	60Hz	6mm	48mm	CMG, FT4
C2G10377	6ft (1.8m)	No	Gripping	Passive	18 Gbps	4K	60Hz	6mm	48mm	CMG, FT4
C2G10378	10ft (3m)	No	Gripping	Passive	18 Gbps	4K	60Hz	6mm	48mm	CMG, FT4
C2G10399	12ft (3.7m)	No	Gripping	Passive	18 Gbps	4K	60Hz	7.3mm	90mm	CMG, FT4
C2G10400	15ft (4.6m)	No	Gripping	Passive	18 Gbps	4K	60Hz	7.3mm	90mm	CMG, FT4
C2G10401	20ft (6.1m)	No	Gripping	Passive	18 Gbps	4K	60Hz	9.5mm	90mm	CMG, FT4
C2G10402	25ft (7.6m)	No	Gripping	Passive	18 Gbps	4K	60Hz	9.5mm	90mm	CMG, FT4
C2G10379	12ft (3.7m)	No	Gripping	Active	18 Gbps	4K	60Hz	6mm	48mm	CMG, FT4
C2G10380	15ft (4.6m)	No	Gripping	Active	18 Gbps	4K	60Hz	6mm	48mm	CMG, FT4
C2G10381	20ft (6.1m)	No	Gripping	Active	18 Gbps	4K	60Hz	6mm	48mm	CMG, FT4
C2G10382	25ft (7.6m)	No	Gripping	Active	18 Gbps	4K	60Hz	6mm	48mm	CMG, FT4
C2G10383	35ft (10.7m)	No	Gripping	Active	18 Gbps	4K	60Hz	9.5mm	76mm	CMG, FT4
C2G10384	50ft (15.2m)	No	Gripping	Active	18 Gbps	4K	60Hz	9.5mm	76mm	CMG, FT4
C2G10385	75ft (22.9m)	No	Gripping	Active	18 Gbps	4K	30Hz	9.5mm	76mm	CMG, FT4
C2G10386	100ft (30.5m)	No	Gripping	Active	18 Gbps	4K	30Hz	9.5mm	76mm	CMG, FT4

PERFORMANCE SERIES Ultra High Speed HDMI® Cable. When quality matters, choose our best 8K cable.

- Ideal for computers and displays requiring high bandwidth solutions and video resolutions up to 8K
- Perfect for high-resolution applications in video production, broadcasting and other business and applications





Item #	Length	Certification	Connector	Active/Passive	Maximum Bandwidth	Maximum Resolution	Maximum Refresh Rate	Cable Diameter	Minimum Bend Radius	Jacket Rating
C2G10452	2ft (0.6m)	Ultra	Gripping	Passive	48 Gbps	8K	60Hz	6mm	48mm	CMG, FT4
C2G10453	3ft (0.9m)	Ultra	Gripping	Passive	48 Gbps	8K	60Hz	6mm	48mm	CMG, FT4
C2G10454	6ft (1.8m)	Ultra	Gripping	Passive	48 Gbps	8K	60Hz	6mm	48mm	CMG, FT4
C2G10455	10ft (3m)	Ultra	Gripping	Passive	48 Gbps	8K	60Hz	6mm	48mm	CMG, FT4
C2G10456	12ft (3.7m)	Ultra	Gripping	Passive	48 Gbps	8K	60Hz	8mm	64mm	CMG, FT4

PERFORMANCE SERIES AOC High Speed HDMI® Cable. For extended length needs.

- Choose active optical HDMI cables when you need to reach up to 300 feet, without sacrificing signal strength or image quality
- Ideal for extending HDMI signals in classrooms, meeting spaces, and other commercial applications requiring high speed HDMI features and video resolutions



Item #	Length	Certification	Connector	Active/Passive	Maximum Bandwidth	Maximum Resolution	Maximum Refresh Rate	Cable Diameter	Minimum Bend Radius	Jacket Rating
C2G41480	15ft (4.6m)	No	Gripping	Active Optical	18 Gbps	4K	60Hz	4.8mm	70mm	CMP
C2G41481	20ft (6.1m)	No	Gripping	Active Optical	18 Gbps	4K	60Hz	4.8mm	70mm	CMP
C2G41482	25ft (7.6m)	No	Gripping	Active Optical	18 Gbps	4K	60Hz	4.8mm	70mm	CMP
C2G41483	35ft (10.7m)	No	Gripping	Active Optical	18 Gbps	4K	60Hz	4.8mm	70mm	CMP
C2G41484	50ft (15.2m)	No	Gripping	Active Optical	18 Gbps	4K	60Hz	4.8mm	70mm	CMP
C2G41485	75ft (22.8m)	No	Gripping	Active Optical	18 Gbps	4K	60Hz	4.8mm	70mm	CMP
C2G41486	100ft (30.5m)	No	Gripping	Active Optical	18 Gbps	4K	60Hz	5.5mm	75mm	CMP
C2G41487	125ft (38.1m)	No	Gripping	Active Optical	18 Gbps	4K	60Hz	5.5mm	75mm	CMP
C2G41488	150ft (45.7m)	No	Gripping	Active Optical	18 Gbps	4K	60Hz	5.5mm	75mm	CMP
C2G41489	200ft (61m)	No	Gripping	Active Optical	18 Gbps	4K	60Hz	5.5mm	75mm	CMP
C2G41490	250ft (76.2m)	No	Gripping	Active Optical	18 Gbps	4K	60Hz	5.5mm	75mm	CMP
C2G41491	300ft (91.4m)	No	Gripping	Active Optical	18 Gbps	4K	60Hz	5.5mm	75mm	CMP

^{*} Performance Series Active Optical HDMI Cables and Performance Series Ultra Flexible Active Cables offer a 5-Year Warranty.



Pro Essentials.



Whether you need HDMI cable for tight spaces or installations with plenum requirements, C2G's Plus Series offers a broad selection of HDMI cables for a variety of applications - at the right price. The Plus Series includes in-wall rated High Speed and Ultra High Speed cables, as well as CL2P and CMP cables for plenum applications, and slim flexible for confined spaces.



наті

PLUS SERIES TAA Premium High Speed HDMI® Cable with Ethernet. For high bandwidth, high-resolution applications.

Approved for use in United States government projects and facilities

Item #	Length	Certification	Connector	Active/Passive	Maximum Bandwidth	Maximum Resolution	Maximum Refresh Rate	Cable Diameter	Minimum Bend Radius	Jacket Rating
C2G50109	3ft (0.9m)	Premium	Standard	Passive	18 Gbps	4K	60Hz	5.8mm	48mm	VW-1
C2G50110	6ft (1.8m)	Premium	Standard	Passive	18 Gbps	4K	60Hz	5.8mm	48mm	VW-1
C2G50111	10ft (3m)	Premium	Standard	Passive	18 Gbps	4K	60Hz	5.8mm	48mm	VW-1

PLUS SERIES Select High Speed HDMI® Cable with Ethernet. In-wall passive cables, available in longer lengths.

• For connecting multimedia source devices in desktop or commercial audio video applications



Item #	Length	Certification	Connector	Active/ Passive	Maximum Bandwidth	Maximum Resolution	Maximum Refresh Rate	Cable Diameter	Minimum Bend Radius	Jacket Rating
50624 or CG50624†	1.5ft (0.46m)	No	Standard	Passive	18 Gbps	4K	60Hz	7.3mm	51mm	CL2
50625 or CG50625†	3ft (0.9m)	No	Standard	Passive	18 Gbps	4K	60Hz	7.3mm	51mm	CL2
50626 or CG50626†	5ft (1.5m)	No	Standard	Passive	18 Gbps	4K	60Hz	7.3mm	51mm	CL2
50627 or CG50627†	6ft (1.8m)	No	Standard	Passive	18 Gbps	4K	60Hz	7.3mm	51mm	CL2
50628 or CG50628†	10ft (3m)	No	Standard	Passive	18 Gbps	4K	60Hz	7.3mm	51mm	CL2
50629 or CG50629†	12ft (3.7m)	No	Standard	Passive	18 Gbps	4K	60Hz	7.3mm	51mm	CL2
50630 or CG50630†	15ft (4.6m)	No	Standard	Passive	18 Gbps	4K	60Hz	8.8mm	88mm	CL2
50631 or CG50631†	16.5ft (5m)	No	Standard	Passive	18 Gbps	4K	60Hz	8.8mm	88mm	CL2
50632 or CG50632†	20ft (6.1m)	No	Standard	Passive	18 Gbps	4K	60Hz	8.8mm	88mm	CL2
50633 or CG50633†	25ft (7.6m)	No	Standard	Passive	18 Gbps	4K	60Hz	10mm	70mm	CL2
50634 or CG50634† ‡	35ft (10.7m)	No	Standard	Passive	4.95 Gbps	1080p	60Hz	10mm	70mm	CL2
50635 or CG50635† ‡	40ft (12.2m)	No	Standard	Passive	4.95 Gbps	1080p	60Hz	10mm	70mm	CL2
50636 or CG50636† ‡	50ft (15.2m)	No	Standard	Passive	4.95 Gbps	1080p	60Hz	10mm	70mm	CL2

PLUS SERIES Ultra High Speed HDMI® Cable. For high bandwidth, high-resolution applications.

Ideal for high-resolution applications in video production, broadcasting and other business applications



Item #	Length	Certification	Connector	Active/Passive	Maximum Bandwidth	Maximum Resolution	Maximum Refresh Rate	Cable Diameter	Minimum Bend Radius	Jacket Rating
C2G10410	3ft (0.9m)	Ultra	Standard	Passive	48 Gbps	8K	60Hz	6mm	60mm	CL2
C2G10411	6ft (1.8m)	Ultra	Standard	Passive	48 Gbps	8K	60Hz	6mm	60mm	CL2
C2G10412	10ft (3m)	Ultra	Standard	Passive	48 Gbps	8K	60Hz	6mm	60mm	CL2
C2G10413	12ft (3.7m)	Ultra	Standard	Passive	48 Gbps	8K	60Hz	8mm	80mm	CL2

[†] Some legacy systems use the 5-digit part number while others use the CG notation for numbers. Contact your Legrand AV sales representative with questions.





[‡] This is a Standard HDMI Cable



PLUS SERIES Slim Flexible High Speed HDMI® Cable with Ethernet. Super slim and highly flexible for tight spaces.

- Space-saving design: low profile connector and slim cable easily fits behind flat panel displays or equipment racks
- Available in 2-packs (C2G21006 & C2G21007) and 3-packs (C2G21008 & C2G21009)



Item #	Length	Certification	Connector	Active/ Passive	Maximum Bandwidth	Maximum Resolution	Maximum Refresh Rate	Cable Diameter	Minimum Bend Radius	Jacket Rating
41361 or CG41361†	1ft (0.3m)	No	Low Profile	Passive	18 Gbps	4K	60Hz	3.6mm	25.4mm	VW-1
41362 or CG41362†	2ft(0.6m)	No	Low Profile	Passive	18 Gbps	4K	60Hz	3.6mm	25.4mm	VW-1
41363 or CG41363†	3ft (0.9m)	No	Low Profile	Passive	18 Gbps	4K	60Hz	3.6mm	25.4mm	VW-1
41364 or CG41364†	6ft (1.8m)	No	Low Profile	Passive	18 Gbps	4K	60Hz	3.6mm	25.4mm	VW-1
C2G41398 ‡	10ft (3m)	No	Low Profile	Passive	10.2 Gbps	1080p	60Hz	3.6mm	25.4mm	VW-1
C2G21006-2PK	3ft (0.9m)	No	Low Profile	Passive	18 Gbps	4K	60Hz	3.6mm	25.4mm	VW-1
C2G21008-3PK	3ft (0.9m)	No	Low Profile	Passive	18 Gbps	4K	60Hz	3.6mm	25.4mm	VW-1
C2G21009-3PK	6ft (1.8m)	No	Low Profile	Passive	18 Gbps	4K	60Hz	3.6mm	25.4mm	VW-1
C2G21007-2PK	6ft (1.8m)	No	Low Profile	Passive	18 Gbps	4K	60Hz	3.6mm	25.4mm	VW-1

PLUS SERIES CMP Standard HDMI® Cable. For plenum applications needing CMP.

• For plenum space above dropped ceilings or under raised floors in schools, hospitals and other commercial buildings



Item #	Length	Certification	Connector	Active/Passive	Maximum Bandwidth	Maximum Resolution	Maximum Refresh Rate	Cable Diameter	Minimum Bend Radius	Jacket Rating
41190 or CG41190†	15ft (4.6m)	No	Standard	Passive	4.95 Gbps	1080p	60Hz	8.4mm	125.7mm	CMP
41191 or CG41191†	25ft (7.6m)	No	Standard	Passive	4.95 Gbps	1080p	60Hz	8.4mm	125.7mm	CMP
41192 or CG41192†	35ft (10.7m)	No	Standard	Passive	4.95 Gbps	1080p	60Hz	8.4mm	125.7mm	CMP
41193 or CG41193†	50ft (15.2m)	No	Standard	Passive	4.95 Gbps	1080p	60Hz	8.4mm	125.7mm	CMP

PLUS SERIES CL2P Standard HDMI® Cable. For CL2P plenum installations.

· For plenum space above dropped ceilings or under raised floors in schools, hospitals and other commercial buildings



Item #	Length	Certification	Connector	Active/Passive	Maximum Bandwidth	Maximum Resolution	Maximum Refresh Rate	Cable Diameter	Minimum Bend Radius	Jacket Rating
42528 or CG42528†	15ft (4.6m)	No	Gripping	Passive	4.95 Gbps	1080p	60Hz	9mm	135mm	CL2P
42529 or CG42529†	25ft (7.6m)	No	Gripping	Passive	4.95 Gbps	1080p	60Hz	9mm	135mm	CL2P
42530 or CG42530†	35ft (10.7m)	No	Gripping	Passive	4.95 Gbps	1080p	60Hz	9mm	135mm	CL2P
42531 or CG42531†	40ft (12.2m)	No	Gripping	Passive	4.95 Gbps	1080p	60Hz	9mm	135mm	CL2P
42532 or CG42532†	50ft (15.2m)	No	Gripping	Passive	4.95 Gbps	1080p	60Hz	9mm	135mm	CL2P

PLUS SERIES Active High Speed HDMI® Cable with Ethernet. For resolutions up to 4K.

• Choose active HDMI cable for distances of 15 feet or more to ensure outstanding picture and sound quality



Item #	Length	Certification	Connector	Active/Passive	Maximum Bandwidth	Maximum Resolution	Maximum Refresh Rate	Cable Diameter	Minimum Bend Radius	Jacket Rating
41412 or CG41412†	15ft (4.6m)	No	Standard	Active	18 Gbps	4K	60Hz	5.1mm	51mm	CL3
41413 or CG41413†	25ft (7.6m)	No	Standard	Active	18 Gbps	4K	60Hz	6.0mm	60mm	CL3
41414 or CG41414†	35ft (10.7m)	No	Standard	Active	18 Gbps	4K	60Hz	8.5mm	85mm	CL3
41415 or CG41415†	50ft (15.2m)	No	Standard	Active	18 Gbps	4K	60Hz	8.5mm	85mm	CL3
41368 or CG41368†	75ft (22.8m)	No	Standard	Active	10.2 Gbps	4K	30Hz	8.5mm	85mm	CL3
41369 or CG41369†	100ft (30.5m)	No	Standard	Active	10.2 Gbps	4K	30Hz	8.5mm	85mm	CL3

[†] Some legacy systems use the 5-digit part number while others use the CG notation for numbers. Contact your Legrand AV sales representative with questions.


[‡] This is a Standard HDMI Cable



Your go-to for basic 4K HDMI cable. C2G's Core Series provides you with reliable cables for office or commercial use.

- Standard jacket rating, standard connector
- Gold-plated connectors for increased electrical conductivity and enhanced durability
- Good flexibility

- Available in one, two and three-packs in 3 ft,
 6 ft and 10 ft lengths (0.9m, 1.8m, 3m)
- Backed by a lifetime warranty for peace of mind



- For connecting computers, projectors and other HDMI devices to monitors and displays
- Available in 2-packs (C2G21000, C2G21001, C2G21002) and 3-packs (C2G21003, C2G21004, C2G21005)



Item #	Length	Certification	Connector	Active/Passive	Maximum Bandwidth	Maximum Resolution	Maximum Refresh Rate	Cable Diameter	Minimum Bend Radius	Jacket Rating
56781 or CG56781†	1ft (0.3m)	No	Standard	Passive	18 Gbps	4K	60Hz	6mm	48mm	VW-1
50606 or CG50606†	1.5ft (0.5m)	No	Standard	Passive	18 Gbps	4K	60Hz	6mm	48mm	VW-1
50607 or CG50607†	2ft (0.6m)	No	Standard	Passive	18 Gbps	4K	60Hz	6mm	48mm	VW-1
56782 or CG56782†	3ft (0.9m)	No	Standard	Passive	18 Gbps	4K	60Hz	6mm	48mm	VW-1
50608 or CG50608†	4ft (1.2m)	No	Standard	Passive	18 Gbps	4K	60Hz	6mm	48mm	VW-1
50609 or CG50609†	5ft (1.5m)	No	Standard	Passive	18 Gbps	4K	60Hz	6mm	48mm	VW-1
56783 or CG56783†	6ft (1.8m)	No	Standard	Passive	18 Gbps	4K	60Hz	6mm	48mm	VW-1
50610 or CG50610†	8ft (2.4m)	No	Standard	Passive	18 Gbps	4K	60Hz	6mm	48mm	VW-1
56784 or CG56784†	10ft (3m)	No	Standard	Passive	18 Gbps	4K	60Hz	6mm	48mm	VW-1
50611 or CG50611†	12ft (3.7m)	No	Standard	Passive	18 Gbps	4K	60Hz	7.3mm	58.4mm	VW-1
50612 or CG50612†	15ft (4.6m)	No	Standard	Passive	18 Gbps	4K	60Hz	7.3mm	58.4mm	VW-1
C2G50647	20ft (6m)	No	Standard	Passive	18 Gbps	4K	60Hz	8.5mm	68mm	VW-1
C2G50648	25ft (7.2m)	No	Standard	Passive	18 Gbps	4K	60Hz	8.5mm	68mm	VW-1
C2G21000-2PK	3ft (0.9m)	No	Standard	Passive	18 Gbps	4K	60Hz	6mm	48mm	VW-1
C2G21001-2PK	6ft (1.8m)	No	Standard	Passive	18 Gbps	4K	60Hz	6mm	48mm	VW-1
C2G21002-2PK	10ft (3m)	No	Standard	Passive	18 Gbps	4K	60Hz	6mm	48mm	VW-1
C2G21003-3PK	3ft (0.9m)	No	Standard	Passive	18 Gbps	4K	60Hz	6mm	48mm	VW-1
C2G21004-3PK	6ft (1.8m)	No	Standard	Passive	18 Gbps	4K	60Hz	6mm	48mm	VW-1
C2G21004-3PK	10ft (3m)	No	Standard	Passive	18 Gbps	4K	60Hz	6mm	48mm	VW-1

[†] Some legacy systems use the 5-digit part number while others use the CG notation for numbers. Contact your Legrand AV sales representative with questions.

The Adopted Trademarks HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries

