

## MMS4X00-NS-T-AO

Mellanox® MMS4X00-NS Compatible TAA 800GBase-DR8 PAM4 OSFP Transceiver (SMF, 1310nm, 100m, 2xMPO, DOM, CMIS 5.0) Ethernet Only

### Features

- OSFP MSA Compliant
- Supports both Ethernet and InfiniBand NDR
- 8x100G PAM4/8x50G PAM4 data rates
- Compliant with IEEE 802.3ck-2022: 8x100GAUI-1 C2M electrical interface
- EML transmitter and PIN PD receiver
- Compliant with IEEE 802.3cu-2021: 8x100GBASE-DR optical interface
- Class 1 Laser
- Cooled 1310 EML Laser
- RoHS Compliant and Lead-Free
- Operating Temperature: 0 to 70 Celsius



### Applications

- 2x400GBase Ethernet

### Product Description

This Mellanox® MMS4X00-NS compatible OSFP transceiver provides 800GBase-DR8 throughput up to 100m over single-mode fiber (SMF) using a wavelength of 1310nm via a 2xMPO connector. It is guaranteed to be 100% compatible with the equivalent Mellanox® transceiver. This easy to install, hot swappable transceiver has been programmed, uniquely serialized and data-traffic and application tested to ensure that it will initialize and perform identically. Digital optical monitoring (DOM) support is also present to allow access to real-time operating parameters. This transceiver is Trade Agreements Act (TAA) compliant. We stand behind the quality of our products and proudly offer a limited lifetime warranty.

AddOn's transceivers are RoHS compliant and lead-free.

TAA refers to the Trade Agreements Act (19 U.S.C. & 2501-2581), which is intended to foster fair and open international trade. TAA requires that the U.S. Government may acquire only "U.S. – made or designated country end products."



## Absolute Maximum Ratings

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
Power Supply Voltage	Vcc	-0.5		3.6	V	
Storage Temperature	Tstg	-40		85	°C	
Operating Case Temperature	Tc	0		70	°C	
Relative Humidity (Non-Condensing)	RH	15		85	%	
Data Rate			106.25		Gbps	
			53.125		Gbps	
Modulation Format			PAM4			

## Electrical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
Power Supply Voltage	Vcc	3.13	3.3	3.47	V	
Module Supply Current	Icc			5.1	A	
Power Dissipation	P <sub>DISS</sub>			16	W	
<b>Transmitter</b>						
<b>Input Differential Impedance</b>	ZIN	90	100	110	Ω	
<b>Differential Data Input Swing</b>	V <sub>IN,pp</sub>			900	mVp-p	
<b>DC Common-Mode Input Voltage</b>		-350		2850	mV	
<b>Receiver</b>						
<b>Differential Data Output Swing</b>	V <sub>OUT</sub>			900	mV	
<b>Output Differential Impedance</b>	Z <sub>OUT</sub>	90	100	110	Ω	1
<b>Dual Function Signals</b>						
INT/RSTn	V_INT/RSTn1	0.000	0.000	1.000	V	2
	V_INT/RSTn2	0.000	0.000	1.000	V	3
	V_INT/RSTn3	1.500	1.900	2.250	V	4
	V_INT/RSTn4	2.750	3.000	3.465	V	5
LPWn/PRSn	V_LPWn/PRSn_1	0.000	0.950	1.100	V	6
	V_LPWn/PRSn_2	1.400	1.700	2.250	V	7
	V_LPWn/PRSn_3	2.750	3.300	3.465	V	8

### Notes:

1. Internally AC coupled but requires an external 100Ω differential load termination.
2. INT/RSTn voltage for no module.
3. INT/RSTn voltage for module installed, H\_RSTn=Low.
4. INT/RSTn voltage for module installed, H\_RSTn=High, M\_INT=Low.
5. INT/RSTn voltage for module installed, H\_RSTn=High, M\_INT=High.

6. LPWn/PRSn for module installed, H\_LPWn=Low.
7. LPWn/PRSn for module installed, H\_LPWn=High.
8. LPWn/PRSn for no module.

### Optical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
<b>Transmitter</b>						
<b>Average Launch Per Lane</b>	Po(100G)	-2.9		4	dBm	1
	Po(50G)	-5.1		3	dBm	1
<b>Outer Optical Modulation Amplitude Per Lane</b>	Poma(100G)	-0.8		4.2	dBm	1
	Poma(50G)	-3		2.8	dBm	1
<b>Extinction Ratio</b>	ER	3.5			dB	2,3
<b>Lane Wavelengths</b>	$\lambda$	1304.5	1311	1317.5	nm	
<b>Side-Mode Suppression Ratio</b>	SMSR	30			dB	
<b>Transmitter and Dispersion Penalty Eye Closure for 100Gbps PAM4 Per Lane</b>	TDECQ1			3.4	dB	2
<b>Transmitter and Dispersion Penalty Eye Closure for 50Gbps PAM4 Per Lane</b>	TDECQ2			3.2	dB	3
<b>Launch Power in OMAouter Minus TDECQ for 100Gbps PAM4 Per Lane</b>	OMA-TDECQ	-2.2			dBm	2
<b>Launch Power in OMAouter Minus TDECQ for 50Gbps PAM4 Per Lane</b>	OMA-TDECQ	-4.4			dBm	3
<b>Average Launch Power of Off Transmitter</b>	Poff			-15	dBm	
<b>Optical Return Loss Tolerance</b>	ORLT			21.4	dB	
<b>Transmitter Reflectance</b>				-26	dB	
<b>Receiver (10G)</b>						
<b>Lane Wavelengths</b>		1304.5	1311	1317.5	nm	
<b>100G Receiver Sensitivity (OMA)</b>				-3.9	dBm	4
<b>50G Receiver Sensitivity (OMA)</b>				-6.1	dBm	5
<b>Receiver Overload Per Lane (Pavg)</b>		4			dBm	
<b>Damage Threshold Per Lane</b>		5			dBm	
<b>Receive Power Per Lane (OMAouter)</b>				4.2	dBm	
<b>Receiver Reflectance</b>				-26	dB	
<b>LOS De-Assert</b>				-10	dBm	
<b>LOS Assert</b>		-16			dBm	
<b>LOS Hysteresis</b>		0.5			dB	

### Notes:

1. Class 1 Laser Safety per FDA/CDRH and EN (IEC) 60825 regulations.
2. Measured with SSPRQ test pattern, @106.25Gbps PAM4.
3. Measured with SSPRQ test pattern, @53.125Gbps PAM4.

4. Measured with PRBS31Q test pattern, @53.125GBd, PAM4, and BER<2.4E<sup>-4</sup>.
5. Measured with PRBS31Q test pattern, @26.5625GBd, PAM4, and BER<2.4E<sup>-4</sup>.

### Pin Descriptions


Pin	Symbol	Name/Description	Logic	Plug Sequence	Direction	Notes
1	GND	Module Ground.		1		
2	Tx2+	Transmitter Data Non-Inverted.	CML-I	3	Input from Host	
3	Tx2-	Transmitter Data Inverted.	CML-I	3	Input from Host	
4	GND	Module Ground.		1		
5	Tx4+	Transmitter Data Non-Inverted.	CML-I	3	Input from Host	
6	Tx4-	Transmitter Data Inverted.	CML-I	3	Input from Host	
7	GND	Module Ground.		1		
8	Tx6+	Transmitter Data Non-Inverted.	CML-I	3	Input from Host	
9	Tx6-	Transmitter Data Inverted.	CML-I	3	Input from Host	
10	GND	Module Ground.		1		
11	Tx8+	Transmitter Data Non-Inverted.	CML-I	3	Input from Host	
12	Tx8-	Transmitter Data Inverted.	CML-I	3	Input from Host	
13	GND	Module Ground.		1		
14	SCL	2-Wire Serial Interface Clock.	LVCMOS-I/O	3	Bi-Directional	1
15	Vcc	+3.3V Power.		2	Power from Host	
16	Vcc	+3.3V Power.		2	Power from Host	
17	LPWn/PRSn	Low-Power Mode/Module Present.	Multi-Level	3	Bi-Directional	2
18	GND	Module Ground.		1		
19	Rx7-	Receiver Data Inverted.	CML-O	3	Output to Host	
20	Rx7+	Receiver Data Non-Inverted.	CML-O	3	Output to Host	
21	GND	Module Ground.		1		
22	Rx5-	Receiver Data Inverted.	CML-O	3	Output to Host	
23	Rx5+	Receiver Data Non-Inverted.	CML-O	3	Output to Host	
24	GND	Module Ground.		1		
25	Rx3-	Receiver Data Inverted.	CML-O	3	Output to Host	
26	Rx3+	Receiver Data Non-Inverted.	CML-O	3	Output to Host	
27	GND	Module Ground.		1		
28	Rx1-	Receiver Data Inverted.	CML-O	3	Output to Host	
29	Rx1+	Receiver Data Non-Inverted.	CML-O	3	Output to Host	
30	GND	Module Ground.		1		
31	GND	Module Ground.		1		
32	Rx2+	Receiver Data Non-Inverted.	CML-O	3	Output to Host	

<b>33</b>	Rx2-	Receiver Data Inverted.	CML-O	3	Output to Host	
<b>34</b>	GND	Module Ground.		1		
<b>35</b>	Rx4+	Receiver Data Non-Inverted.	CML-O	3	Output to Host	
<b>36</b>	Rx4-	Receiver Data Inverted.	CML-O	3	Output to Host	
<b>37</b>	GND	Module Ground.		1		
<b>38</b>	Rx6+	Receiver Data Non-Inverted.	CML-O	3	Output to Host	
<b>39</b>	Rx6-	Receiver Data Inverted.	CML-O	3	Output to Host	
<b>40</b>	GND	Module Ground.		1		
<b>41</b>	Rx8+	Receiver Data Non-Inverted.	CML-O	3	Output to Host	
<b>42</b>	Rx8-	Receiver Data Inverted.	CML-O	3	Output to Host	
<b>43</b>	GND	Module Ground.		1		
<b>44</b>	INT/RSTn	Module Interrupt/Module Reset.	Multi-Level	3	Bi-Directional	2
<b>45</b>	Vcc	+3.3V Power.		2	Power from Host	
<b>46</b>	Vcc	+3.3V Power.		2	Power from Host	
<b>47</b>	SDA	2-Wire Serial Interface Data.	LVCMOS-I/O	3	Bi-Directional	1
<b>48</b>	GND	Module Ground.		1		
<b>49</b>	Tx7-	Transmitter Data Inverted.	CML-I	3	Input from Host	
<b>50</b>	Tx7+	Transmitter Data Non-Inverted.	CML-I	3	Input from Host	
<b>51</b>	GND	Module Ground.		1		
<b>52</b>	Tx5-	Transmitter Data Inverted.	CML-I	3	Input from Host	
<b>53</b>	Tx5+	Transmitter Data Non-Inverted.	CML-I	3	Input from Host	
<b>54</b>	GND	Module Ground.		1		
<b>55</b>	Tx3-	Transmitter Data Inverted.	CML-I	3	Input from Host	
<b>56</b>	Tx3+	Transmitter Data Non-Inverted.	CML-I	3	Input from Host	
<b>57</b>	GND	Module Ground.		1		
<b>58</b>	Tx1-	Transmitter Data Inverted.	CML-I	3	Input from Host	
<b>59</b>	Tx1+	Transmitter Data Non-Inverted.	CML-I	3	Input from Host	
<b>60</b>	GND	Module Ground.		1		


**Notes:**

1. Open-drain with pull-up resistor on the host.
2. See pin assignments below for the required circuit.


## Electrical Pin-Out Details




## Recommended Host Board Power Supply Filter Network




## Block Diagram



## Recommended Application Interface Block Diagram



## Mechanical Specifications



## About AddOn Networks

In 1999, AddOn Networks entered the market with a single product. Our founders fulfilled a severe shortage for compatible, cost-effective optical transceivers that compete at the same performance levels as leading OEM manufacturers. Adhering to the idea of redefining service and product quality not previously had in the fiber optic networking industry, AddOn invested resources in solution design, production, fulfillment, and global support.

Combining one of the most extensive and stringent testing processes in the industry, an exceptional free tech support center, and a consistent roll-out of innovative technologies, AddOn has continually set industry standards of quality and reliability throughout its history.

Reliability is the cornerstone of any optical fiber network and is engrained in AddOn's DNA. It has played a key role in nurturing the long-term relationships developed over the years with customers. AddOn remains committed to exceeding industry standards with certifications from ranging from NEBS Level 3 to ISO 9001:2005 with every new development while maintaining the signature reliability of its products.



## U.S. Headquarters

Email: [sales@addonnetworks.com](mailto:sales@addonnetworks.com)

Telephone: +1 877.292.1701

Fax: 949.266.9273

## Europe Headquarters

Email: [salesupportemea@addonnetworks.com](mailto:salesupportemea@addonnetworks.com)

Telephone: +44 1285 842070