

GVM-2000 Smart Gigabit RJ45-SFP Media Converter, Compatible with 19-inch rack-mountable chassis

Product Images



Short Description

- 1 × 10/100/1000BASE-T RJ45 port and 1 × 100/1000BASE-X SFP port
- Supports QoS, ERPS, IGMP, VLAN, ACL functions
- Fully compatible with 19-inch rack-mountable chassis for easy integration
- Provides 6 kV surge protection and 6 kV contact / 8 kV air ESD protection
- Supports management via Web browser and SNMP

Description

The LevelOne GVM-2000 is a Smart Gigabit Media Converter designed to efficiently bridge Ethernet signals between 10/100/1000Base-T and 100/1000Base-X SFP transceiver interfaces. It supports both half- and full-duplex operation and provides versatile fiber connectivity options for flexible deployment in various network environments.

Equipped with an intuitive web-based management interface, the GVM-2000 enables simplified configuration, monitoring, and maintenance—either locally or via SNMP. Users can easily manage key functions such as bandwidth control, duplex mode, port speed, and VLAN configuration. The converter is also compatible with the 19-inch rack-mountable 14-slot Media Converter Chassis (CVH-2000), delivering reliable performance, centralized management, and streamlined network operation.

Additional Information

Features.	System Management • Web browser, SNMP • Display system information. IP address, subnet mask and gateway item can be configured • Reset user name and password • Recover the default configuration • Reboot switch • Firmware upgrade by HTTP protocol through Ethernet network Port Management • Auto-negotiation • Port Enable/Disable • Flow Control • Bandwidth control per port • Port Mirror VLAN • IEEE 802.1Q tag-based VLAN • Up to 4096 VLAN IDs QoS • Traffic classification based, strict priority and WRR • 8-level priority for switching • Traffic classification • CoS/802.1p • DSCP ACL • ACL based port MAC • Dynamic Address • Static Address Ring protocol • Supports ERPS, and complies with ITU-TG.8032 • Recovery time <500ms Loop Detection • Enable/Disable IGMP Snooping • Enable/Disable Configuration Management • Configuration upload/download through HTTP
Fiber Optical Mode.	Both
Media Interface.	RJ45 to SFP
PoE Supported.	No
Manageable.	Yes
Grade.	Commercial
Approval and Compliance.	• CE • UKCA • FCC CFR Title 47, Part 15, Subpart B Class B • ANSI C63.4:2014 • RoHS
Operating humidity.	5% RH ~ 90% RH
Operating temperature.	0°C ~ 45°C
Storage humidity.	5% RH ~ 90% RH
Storage temperature.	-40°C ~ 70°C
Package Contents.	• GVM-2000 • Power Adapter with Power Plug • Quick Installation Guide • Declaration of Conformity
Color.	Black
Model Number.	GVM-2000
Dimensions (W x D x H).	94 x 71 x 26 mm
Product weight (kg).	0.177 kg

Data Rate.	1Gbps
Indicators.	<ul style="list-style-type: none"> • PWR: Green, power supply • L/A (Right): Green, Link/Active for UTP • FX (Left): Green, Link/Active for Fiber
Jumbo frame (KB).	9
Mount.	Desk mount
MTBF.	>400K(SR332)
Power consumption.	10 W
Power supply.	5VDC/2A (Power Adapter with Power Plug)
Power supply included.	Yes
Standards.	IEEE 802.3 10-BASE-T, Ethernet, IEEE 802.3u 100-BASE-TX, Fast Ethernet, IEEE 802.3ab 1000BASE-T, Gigabit Ethernet, IEEE 802.3az Energy-Efficient Ethernet, IEEE802.3z 1000Base-SX/LX

