

128830 USB 2.0 Cable, USB-C Male to USB-A Male, 0.3m

Product Images





Short Description

- **Connector A:** USB-C Male
- **Connector B:** USB-A Male
- **USB standard:** USB 2.0
- **Data transfer rate:** Up to 480 Mbps
- **Charging current:** Up to 3A
- **Shielding:** Double shielding for stable transmission
- **Connector plating:** Nickel plated
- **Jacket:** PVC
- **Length:** 0.3 m
- **Function:** Charging & data sync

Description

The 128830 USB 2.0 USB-C to USB-A cable offers a compact and reliable solution for charging and data synchronization between USB-C devices and standard USB-A ports.

Supporting data transfer speeds of up to 480 Mbps, this short-length cable is ideal for close-range connections such as power banks, docking stations, laptops, and USB hubs. Double shielding helps reduce electromagnetic interference and ensures stable, error-free signal transmission.

With support for up to 3A output current, the cable enables efficient charging for USB-C smartphones, tablets, and accessories. Nickel-plated connectors and a durable PVC jacket ensure dependable performance and long service life in everyday use.

Additional Information

Angled Plug.	No
Shielded.	No
Connector 1.	USB-A, male
Connector 2.	USB-C, male
Approval and Compliance.	ROHS, REACH
Package Contents.	USB 2.0 C to A, Cable, M/M, 0.3m
Color.	Black
Model Number.	128830
Cable Length.	0.3m
Dimensions (W x D x H).	4.5 x 4.5 x 300 mm
Product weight (kg).	0.02
Conductor material.	Copper
Data Rate.	480Mbps
Standards.	USB 2.0

