



QSW-1105-5T

| | |
|-------------------------------|--|
| Management Type | Unmanaged |
| Number of Ports | 5 |
| 2.5GbE (RJ45) | 5 |
| Power Supply Description | Adapter |
| Max. Power Consumption | 12 W |
| Input Power Type | DC |
| Input Voltage Range | 12V |
| MAC Address Table | 16K |
| Total Non-Blocking Throughput | 12.5Gbps |
| Switching Capacity | 25Gbps |
| Fan | Fanless |
| Fanless | Yes |
| Supported Standards | IEEE 802.3 Ethernet IEEE 802.3u 100BASE-T IEEE 802.3ab 1000BASE-T IEEE 802.3bz 2.5GBase-T IEEE 802.3x Full-Duplex Flow Control |
| Form Factor | Desktop |
| LED Indicators | Per Port: Speed/Link/Activity Loop LED: Loop Per System: Power/Status |
| Dimensions (HxWxD) | 34 x 180 x 145 mm |
| Weight (Net) | 0.577 kg |
| Operating Temperature | 0°C to 40°C (32°F to 104°F) |
| Relative Humidity | 10% to 90% (non-condensing) |
| Certifications | FCC, CE, BSMI, VCCI, LVD, CCC, KCC, ASNZ |

| | |
|----------------------------|---------|
| Electromagnetic Compliance | Class B |
| Jumbo Frames | 9K |
| Warranty | 2 Years |

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test

Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.