




4-Pack SFP Multi-Mode LC Module (550m)


TEG-MGBSX/4 (v3.3R)


- Includes four TEG-MGBSX SFP modules
- Compliant with IEEE 802.3z Gigabit Ethernet
- ANSI Fiber Channel compliant
- Small Form-Factor Pluggable (SFP) and Multi-Source Agreement (MSA) compliant
- Supports data rates of up to 1.25Gbps
- Transmission distance of up to 550m (1804 ft.)
- Low Electromagnetic Interference (EMI) design
- Supports 850nm multi-mode network transmissions
- Duplex LC optical interface
- · Low power consumption

TRENDnet's 4-Pack SFP Multi-Mode LC Module, model TEG-MGBSX/4, includes four fiber gigabit SFP modules that are compatible with standard SFP slots found on network switches and fiber media converters. Each Multi-Mode SFP module is equipped with a duplex LC fiber connection interface, and supports gigabit multi-mode fiber connections for long distance networking applications.









Fiber Applications

Long distance fiber networking for manufacturing, business parks, and school campus applications.

Fiber Mode/Distance


Multi-Mode transceiver spans distances up to 550m (1804 ft.) at gigabit speeds.

Compatibility

Hot-pluggable with an MSA compliant SFP slot, and compatible with fiber cables with LC-type duplex connectors.

NETWORKING SOLUTION







FEATURES



Hot-Pluggable SFP
Hot-pluggable SFP transceiver
compatible with an MSA compliant
SFP slot



Fiber Wavelength
Compatible with multi-mode 850nm transmissions



Fiber DistanceSupports networking for distances up to 550m (1804 ft.)

Fib LC-

Fiber Interface
LC-type duplex connector

SPECIFICATIONS

Standards

- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3z

Device Interface

- SFP MSA Compliant
- · LC duplex connector

Data Transfer Rate

• 1.25Gbps

Wavelength

• 850nm

Optical Output Power

• -9 ~ -3 dBm

Distance

• 550m (1804 ft.)

Special Features

- Hot pluggable
- · Metal enclosure

Sensitivity

• -20 dBm

Power

• Max. Consumption: 0.8W

Operating Temperature

• 0° - 70° C (32° - 158 °F)

Operating Humidity

• Max. 85% non-condensing

Dimensions

• 57 x 13 x 12 mm (2.2 x 0.5 x 0.5 in.) per unit

Weight

• 18g (0.6 oz.) per unit

Certifications

- CE
- FCC

Warranty

• 3 year

Package Contents

- 4 x TEG-MGBSX
- Quick Installation Guide

All references to speed are for comparison purposes only. Product specifications, size, and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.